

RF 173.937USH 10/2/06

- 2 -

In the claims:

Please amend the claims as shown below:

- 5 1. (Currently amended) An apparatus for installation at shooting ranges, comprising:  
a housing ~~(12)~~ having a resilient top layer ~~(24)~~ and a flexible bottom layer ~~(26)~~, the layer ~~(26)~~ extending along an inclined bottom surface ~~(28)~~ and over an upwardly protruding  
10 support member ~~(30)~~ to a front side ~~(34)~~, the top layer ~~(24)~~ being attached to the layer ~~(26)~~ at the front side ~~(34)~~ to form a water-tight container ~~(25)~~;  
a stationary non-flowable material ~~(16)~~ tightly packed in the container ~~(25)~~ for adhering to projectiles that have  
15 penetrated through the top layer ~~(24)~~; and  
the inclined bottom surface ~~(28)~~ being inclined at an angle ~~(20)~~ relative to a horizontal plane ~~(21)~~, the angle ~~(20)~~ being less than an angle of repose ~~(23)~~ of the granulated material ~~(16)~~; and -  
20 a supporting member being placed on top of the member and the member extending an entire width (W) of the housing, the housing having a dewatering means disposed therein.
- 25 2. (Currently amended) An apparatus for installation at shooting ranges, comprising:  
a housing having a resilient top layer and a flexible bottom

RF 173.93708V 10/2/06

- 3 -

layer, the layer extending along an inclined bottom surface and over an upwardly protruding support member to a front side, the top layer being attached to the layer at the front side to form a water-tight container;

- 5 a stationary non-flowable material tightly packed in the container for adhering to projectiles that have penetrated through the top layer;  
the inclined bottom surface being inclined at an angle relative to a horizontal plane, the angle being less than an  
10 angle of repose of the granulated material;

~~The apparatus according to claim 1 wherein the housing (12) is being in operative engagement with a rectangular housing (14) filled with a granulated material (116) and having a resilient front layer (106) for permitting projectiles (117) to pass therethrough; and ~~~

- 15 the housing having a horizontal segment disposed at an upper end of the housing and in front of the front layer, the segment and the front layer having a gap defined therebetween.

20

3. (Canceled)

4. (Canceled)

- 25 5. (Currently amended) The apparatus according to claim 4 1 wherein the bottom layer (26) and the upper layer (24) is

RF 173.937USN 10/2/06

- 4 -

attached to the member ~~(32)~~.

6. (Currently amended) The apparatus according to claim 2 wherein the housing ~~(14)~~ has a watertight bottom layer ~~(120)~~ extending upwardly on a portion of an inside of the front layer ~~(106)~~.

7. (Currently amended) The apparatus according to claim 1 wherein the member ~~(30)~~ is substantially perpendicular to the bottom surface ~~(28)~~ and the bottom layer ~~(26)~~.

8. (Currently amended) The apparatus according to claim 2 wherein the housing ~~(14)~~ has an L-shaped concrete wall ~~(58)~~ for supporting a lid ~~(60)~~.

9. (Currently amended) The apparatus according to claim 8 wherein the lid ~~(60)~~ has a downwardly protruding protector ~~(64)~~.

10. (Currently amended) The apparatus according to claim 1 wherein the apparatus has an inclined bullet diverter ~~(302)~~ disposed at below a set of targets ~~(308)~~.

11. (Currently amended) The apparatus according to claim 1 wherein the housing ~~(12)~~ has a horizontal segment (50) disposed at an upper end ~~(51)~~ of the housing ~~(12)~~.

RP 173.937USH 10/2/06

- 5 -

12. (Currently amended) The apparatus according to claim 1 wherein the bottom layer ~~(26)~~ is attached to the housing box ~~(12)~~ and has an area ~~(27)~~ disposed outside the housing box ~~(12)~~.

13. (Currently amended) The apparatus according to claim 1 wherein the bottom layer ~~(26)~~ extends in a direction to divert water therefrom.